



VECTOR FULL SYNTHETIC SP/GF-6A ENGINE OIL

Vector Full Synthetic SP/GF-6A Engine Oils are the latest iteration in advanced protection for your gasoline-fueled Vector vehicles. Vector Full Synthetic SP/GF-6A Engine Oils are API licensed. These lubricants are designed to perform under extreme conditions, have excellent cold temperature properties, resist thermal breakdown, and exceed the performance requirements of API SP and ILSAC GF-6A licensing categories and are now recommended against Ford Motor Company's LSPI specifications Ford WSS-M2C962-A1 and Ford WSS-M2C961-A1.

TYPICAL PROPERTIES			
SAE	0W-20	5W-20	5W-30
API Service	SP/GF-6A	SP/GF-6A	SP/GF-6A
Kinematic Viscosity cST@40°C cST@100°C	44.89 8.48	48.7 8.88	62.1 10.9
Viscosity Index	173	164	169
CCS Viscosity cP@ C	5880 (-30)	4773 (-30)	4532(-30)
HTHS Viscosity cP@ 150°C	2.4	3.1	2.6
Flash Point, C	206	202	206
Pour Point, C	-48	-45	-42

Note: Values shown above are representative of current production and many vary within modest ranges.



2324 Donald Lee Hollowell Pkwy NW
Atlanta, GA 30318
800-899-0058
atlantafuel.com