

VECTOR FULL SYNTHETIC dexos¹™ GEN3 SP/GF-6A ENGINE OIL

Vector Full Synthetic dexos¹™ Gen 2 SP/GF-6A Engine Oils are the latest iteration in advanced protection for your gasoline-fueled Vector vehicles. Vector Full Synthetic dexos¹™ Gen 3 SP/GF-6A Engine Oils are licensed and approved by General Motors. These lubricants are designed to perform under extreme conditions, have excellent cold temperature properties, resist thermal breakdown, and exceed the performance requirements of API SP and ILSAC GF-6A licensing categories and are now recommended against Ford Motor Company's LSPI specifications Ford WSS-M2C962-A1 and Ford WSS-M2C961-A1.

Vector Full Synthetic dexos¹™ Gen 3 SP/GF-6A Engine Oils are recommended for all types of modern gasoline-fueled vehicles, including high-performance turbo-charged, supercharged, multi-valve fuel inject and gas direct injected engines found in passenger cars, SUV's, light duty vans and trucks. These fluids as ILASAC GF-6A certified, fully backward compatible to GF-5 and earlier certifications as well as all GM and Ford vehicles, and are suitable for a variety of other brand vehicles specifying these viscosity grades. Vector Full Synthetic dexos¹™ Gen 3 SP/GF-6A Engine Oils are API "Resource Conserving" and provide enhanced fuel economy.

| TYPICAL PROPERTIES | | |
|--|-------------|--------------|
| SAE | 0W-20 | 5W-30 |
| API Service | SP/GF-6A | SP/GF-6A |
| dexos ¹ ™ Gen 2 License Number | D33008DA111 | D33009DA111 |
| Kinematic Viscosity cST@40°C cST@100°C | 44.0 8.2 | 61.3 10.9 |
| Viscosity Index | 163 | 171 |
| CCS Viscosity cP@ C | 5500 (-35) | 5000 (-30) |
| HTHS Viscosity cP@ 150°C | 2.6 | 3.2 |
| Flash Point, C | 225 | 230 |
| Pour Point, C | -40 | -40 |

0W-20:

- API SP, SN PLUS
- ILSAC GF-6A, GF-5
- GM dexos¹™ GEN 3
- FORD WSS-M2C962-A1, WSS-M2C947-B1
- CHRYSLER MS-6395
- FOREIGN & DOMESTIC VEHICLES SPECIFYING 0W-20, GM VEHICLES PREVIOUSLY REQUIRING dexos¹™ 5W-20

5W-30:

- API SP, SN PLUS
- ILSAC GF-6A, GF-5
- GM dexos¹™ GEN 3
- FORD WSS-M2C961-A1, WSS-M2C946-B1
- CHRYSLER MS-6395
- FOREIGN & DOMESTIC VEHICLES SPECIFYING 5W-30

Note: Values shown above are representative of current production and many vary within modest ranges.



2324 Donald Lee Hollowell Pkwy NW
Atlanta, GA 30318
800-899-0058
atlantafuel.com